


UI-5220RE-C-HQ PoE Rev.2



Specification

Sensor

Sensor Technology	CMOS Color
Manufacturer	Aptina
Resolution (MPix)	0.36
Resolution (h x v)	752 x 480
ADC	10 bit
Color depth (camera)	12 bit
Pixel Class	WVGA
Sensor Size	1/3"
Shutter	Global shutter
max. fps in Freerun Mode	100.2
Binning Modes	Mono
Subsampling Modes	-
Sensor Model	MT9V032C12STC
Pixel size	6 µm
Optical Size	4.512 mm x 2.880 mm
Optical sensor diagonal	5.35 mm (1/2.99")



Design

Interface	GigE
Lens Mount	C-Mount
I/O In	1 x optodecoupled
I/O Out	1 x optodecoupled
I/O RS-232	-
I/O GPIO	2
I/O I ² C	-
IP code	IP65/67
Dimensions H/W/L	41.0 mm x 53.0 mm x 39.7 mm
Mass	175 g
Power supply	12V - 24V or PoE

UI-5220RE-C-HQ PoE Rev.2

Pin assignment I/O connector

1	Trigger Input (+)
2	Power supply (VCC), 12-24 V DC
3	GPI01
4	Ground (GND)
5	Flash output (+)
6	Flash output (-)
7	Trigger input (-)
8	GPI02

