

# GC1350 / 1350C

## 1.4 Megapixel CCD Camera - Ultra Compact

- High resolution 1.4 megapixels (1360 x 1024)
- Sony 1/2" Progressive scan CCD
- Gigabit Ethernet interface
- Very small and light weight
- Region of Interest readout (AOI partial scan)
- Binning Modes 2x2 to 8x8 and more



Resolution	1360x1024
Sensor Type	1/2" CCD Super HAD progressive scan Sony ICX205
Pixel Size (µm)	4.65 x 4.65
Maximum Frame Rate	20 fps at 1360x1024
Lens Mount	C-mount with adjustable back focus
Digital Interface*	GigE Vision 1.0
Interface Type	IEEE 802.3 1000baseT
Exposure Range	10µs to 60s
Region of Interest (ROI)	Independent x and y control; 1 pixel resolution
Binning	Independent H and V control
Imaging Modes	External Trigger, Fixed frame rate, Software trigger
External Trigger Modes	Rising edge, Falling edge, Any edge, Level high, Level low
External Sync Modes	Trigger ready, Trigger input, Exposing, Readout, Imaging, Strobe, GPO
External Trigger/ Sync Connection	12-pin Hirose
Monochrome Modes	Mono8, Mono16**
Color Modes	Bayer8, Bayer16, RGB24, YUV411, YUV422, YUV444, BGR24, RGBA24, BGRA24
GPIO	1 isolated TTL input, 1 isolated TTL output, 1 non-isolated TTL input, 1 non-isolated TTL output, RS232 I/O
Power Consumption	less than 3 W (12V)
Housing Size	33x46x43 mm
Weight	100 g
Conformity	CE, FCC, RoHS
	Erea includes cample code and driver
SDK	Free - includes sample code and driver

\*GigE Vision™ is a trademark of the Automated Imaging Association \*\*Mono16 is available on monochrome models only.

Specifications are subject to change without notice

Please refer to the Prosilica web site for a full list of specifications

#### Prosilica Inc.

101-3750 North Fraser Way | Burnaby, BC | V5J 5E9 | Canada Tel: 604.875.8855 | Fax: 604.875.8856 | info@prosilica.com

#### About the GC1350 / 1350C

The 1.4 Megapixel GC1350 is a high-resolution CCD camera with Gigabit Ethernet interface (GigE Vision\*). The GC1350 incorporates a high-quality Sony 1/2" CCD sensor providing excellent monochrome and color image quality. The GC1350 runs 20 frames per second at 1360x1024 resolution and even faster with region of interest readout.

#### Applications for the GC1350 include:

- · industrial inspection
- machine vision
- ophthalmology
- · aeronautical and aerospace
- public security, surveillance
- · traffic imaging
- OEM applications

#### The Prosilica Advantage

- Image quality
- High reliability
- High performance
- Ultra-Compact
- Ease of use and integration
- Rich set of camera features

### www.prosilica.com