

## SPECIFICATIONS

Model		WAT-902DM3 (EIA)	WAT-902DM3 (CCIR)
Pick-up element		1/3 inch interline transfer CCD image sensor	
Number of total pixels		811(H) × 508(V)	795(H) × 596(V)
Number of effective pixels		768(H) × 494(V)	752(H) × 582(V)
Unit cell size		6.35μm(H) × 7.4μm(V)	6.5μm(H) × 6.25μm(V)
Synchronizing system		Internal	
Scanning system		2:1 interlace	
Video output		Composite Video, 1Vp-p, 75ohms, unbalanced	
Resolution (H)		570TVL (Center)	
Minimum illumination		0.002lx F1.4	
S/N		More than 52dB (AGC=8dB, $\gamma=1.0$ )	
AE mode	Fixed	1/60, 1/100 sec.	1/50, 1/120 sec.
	EI	1/60 - 1/100000 sec.	1/50 - 1/100000 sec.
AGC		HI: 8 - 40dB / LO: 8 - 22dB	
Gamma characteristics		$\gamma \approx 0.45(\text{ON}) / \gamma = 1.0(\text{OFF})$	
Lens-iris		Video / DC (EIAJ arrangement, Auto-select)	
Back light compensation		ON / OFF	
Mirror image function		ON / OFF	
Power supply		DC+12V±10%	
Power consumption		1.5W (125mA)	
Operating temperature		-10°C - +40°C	
Storage temperature		-30°C - +70°C	
Operating / Storage humidity		Less than 95% RH (Without condensation)	
Lens mount		CS mount	
Weight		Approx. 90g	

※Design and specifications are subject to change without notice.

## DIMENSIONS (mm)

